

SGP

配管用炭素鋼鋼管

寸 法				重 量		クロナシ			シロナシ		シロ付		シロナシ	磨
呼び径		外径	肉厚	P/kg	P/kg	溶協品	高炉品		高炉品				溶協品	溶協品
				長さ			在庫		在庫					
(A)	(B)	(mm)	(mm)	5.5m	4.0m	5.5m	5.5m	4.0m	5.5m	4.0m	5.5m	4.0m	5.5m	5.5m
6A	1/8	10.5	2.0	2.30		◎								
8A	1/4	13.8	2.3	3.59		◎							◎	◎
10A	3/8	17.3	2.3	4.68		◎							◎	◎
15A	1/2	21.7	2.8	7.20	5.24	◎	◎	◎	◎	◎		◎	◎	◎
20A	3/4	27.2	2.8	9.24	6.72	◎	◎	◎	◎	◎		◎	◎	◎
25A	1	34.0	3.2	13.4	9.72	◎	◎	◎	◎	◎		◎	◎	◎
32A	1 1/4	42.7	3.5	18.6	13.5	◎	◎	◎	◎	◎		◎	◎	◎
40A	1 1/2	48.6	3.5	21.4	15.6	◎	◎	◎	◎	◎		◎	◎	
50A	2	60.5	3.8	29.2	21.2	◎	◎	◎	◎	◎		◎	◎	
65A	2 1/2	76.3	4.2	41.1	29.9	◎	◎	◎	◎	◎		◎	◎	
80A	3	89.1	4.2	48.3	35.2	◎	◎	◎	◎	◎		◎	◎	
90A	3 1/2	101.6	4.2	55.6	40.4	◎	◎	◎	◎	◎				
100A	4	114.3	4.5	67.1	48.8	◎	◎	◎	◎	◎		◎	◎	
125A	5	139.8	4.5	82.5		◎	◎		◎				◎	
150A	6	165.2	5.0	109		◎	◎		◎		◎			
175A	7	190.7	5.3	133		◎	◎							
200A	8	216.3	5.8	166		◎	◎		◎					
225A	9	241.8	6.2	198			◎							
250A	10	267.4	6.6	233		◎	◎		◎					
300A	12	318.5	6.9	292		◎	◎		◎					
350A	14	355.6	7.9	372			◎		◎					
400A	16	406.4	7.9	427			◎		◎					
450A	18	457.2	7.9	481			◎							
500A	20	508.0	7.9	536			◎							

◎常備材 ○非常備材 △取扱材