STKM11A E-G

電縫材料管

| 外径 | 肉厚 | 長さ | 在庫 |
|------|------|------|------|
| (mm) | (mm) | (mm) | 1工/中 |
| 6.0 | 1.0 | 3660 | 0 |
| 7.0 | 1.0 | 3660 | 0 |
| 9.0 | 1.0 | 3660 | 0 |
| 8.0 | 1.6 | 3660 | 0 |
| 9.0 | 1.0 | 3660 | 0 |
| 9.5 | 1.0 | 3660 | 0 |
| 9.0 | 1.2 | 3660 | 0 |
| | 1.0 | 3660 | 0 |
| 10.0 | 1.2 | 3660 | 0 |
| | 1.6 | 3660 | 0 |
| 11.0 | 1.0 | 3660 | 0 |
| | 1.0 | 3660 | 0 |
| 12.0 | 1.2 | 3660 | 0 |
| | 1.6 | 5500 | 0 |
| | 1.0 | 5500 | 0 |
| 12.7 | 1.2 | 5500 | 0 |
| | 1.6 | 5500 | 0 |
| 14.0 | 1.0 | 3660 | 0 |
| | 1.2 | 5500 | 0 |
| 15.9 | 1.6 | 5500 | 0 |
| | 2.0 | 5500 | 0 |
| | 1.2 | 5500 | 0 |
| 17.3 | 1.6 | 5500 | 0 |
| 11.3 | 2.3 | 5500 | 0 |
| | 3.0 | 5500 | 0 |
| | 1.0 | 5500 | 0 |
| | 1.2 | 5500 | 0 |
| 19.1 | 1.6 | 5500 | 0 |
| | 2.0 | 5500 | 0 |
| | 2.3 | 5500 | 0 |
| 20.0 | 1.5 | 5500 | 0 |

| 外径 | 肉厚 | 長さ | 在庫 |
|------|------|------|----|
| (mm) | (mm) | (mm) | |
| 21.7 | 2.3 | 5500 | 0 |
| | 3.7 | 5500 | 0 |
| | 4.5 | 5500 | 0 |
| 22.2 | 1.2 | 5500 | 0 |
| | 1.6 | 5500 | 0 |
| | 2.0 | 5500 | 0 |
| | 2.3 | 5500 | 0 |
| | 3.2 | 5500 | 0 |
| 27.2 | 1.6 | 5500 | 0 |
| | 1.2 | 5500 | 0 |
| 28.6 | 1.6 | 5500 | 0 |
| | 2.0 | 5500 | 0 |
| | 1.2 | 5500 | 0 |
| | 1.6 | 5500 | 0 |
| 31.8 | 2.0 | 5500 | 0 |
| | 2.3 | 5500 | 0 |
| | 3.2 | 5500 | 0 |
| | 1.2 | 5500 | 0 |
| | 1.6 | 5500 | 0 |
| | 2.0 | 5500 | 0 |
| 34.0 | 2.3 | 5500 | 0 |
| | 3.2 | 5500 | 0 |
| | 5.0 | 5500 | 0 |
| | 5.5 | 5500 | 0 |
| 35.0 | 1.2 | 5500 | 0 |
| | 2.0 | 5500 | 0 |
| 38.1 | 1.2 | 5500 | 0 |
| | 1.6 | 5500 | 0 |
| | 2.0 | 5500 | 0 |
| | 2.3 | 5500 | 0 |
| 42.7 | 1.2 | 5500 | 0 |
| | 1.6 | 5500 | 0 |
| | 2.0 | 5500 | 0 |
| | 2.3 | 5500 | 0 |
| | 0.0 | FF00 | |

| 外径 | 肉厚 | 長さ | 大 库 |
|-------|------|------|----------------|
| (mm) | (mm) | (mm) | 在庫 |
| 45.0 | 1.2 | 5500 | 0 |
| | 1.6 | 5500 | 0 |
| | 2.0 | 5500 | 0 |
| | 1.6 | 5500 | 0 |
| 40.0 | 2.0 | 5500 | 0 |
| 48.6 | 2.3 | 5500 | 0 |
| | 2.9 | 5500 | 0 |
| | 1.2 | 5500 | 0 |
| 50.0 | 1.6 | 5500 | 0 |
| 50.8 | 2.0 | 5500 | 0 |
| | 2.3 | 6000 | 0 |
| 54.0 | 1.6 | 5500 | \triangle |
| | 2.3 | 5500 | \triangle |
| CO F | 1.6 | 5500 | 0 |
| 60.5 | 2.0 | 5500 | 0 |
| 63.5 | 1.6 | 5500 | 0 |
| 63.5 | 2.6 | 5500 | 0 |
| 70.0 | 1.6 | 5500 | 0 |
| | 1.6 | 5500 | 0 |
| | 2.0 | 5500 | 0 |
| | 2.3 | 5500 | 0 |
| 76.3 | 2.9 | 5500 | 0 |
| 70.5 | 3.2 | 5500 | 0 |
| | 3.5 | 5500 | 0 |
| | 4.0 | 5500 | 0 |
| | 4.5 | 5500 | 0 |
| 82.6 | 2.3 | 5500 | 0 |
| 89.1 | 1.6 | 5500 | 0 |
| | 2.9 | 5500 | 0 |
| | 3.5 | 5500 | 0 |
| | 4.2 | 5500 | 0 |
| | 6.0 | 5500 | 0 |
| 101.6 | 1.6 | 5500 | 0 |
| | 2.6 | 5500 | 0 |
| | 3.2 | 5500 | 0 |
| | 3.5 | 5500 | 0 |
| | 5.0 | 5500 | 0 |

◎ 常備材

○ 非常備材

△ 取扱材

2.6

5500 🔘