

# STKM13C (1/2)

## 冷間引抜鋼管

寸法 (mm)		重量	在庫	寸法 (mm)		重量	在庫	寸法 (mm)		重量	在庫	
外径	肉厚	kg/m		外径	肉厚	kg/m		外径	肉厚	kg/m		
6.0	1.0	0.123	○	14.0	1.2	0.379	○	19.0	1.5	0.647	○	
	1.2	0.142	×		1.5	0.462	◎		2.0	0.838	○	
	1.5	0.166	○		2.0	0.592	◎		2.5	1.02	○	
	2.0	0.197	○		2.5	0.709	◎		3.0	1.18	○	
7.0	1.0	0.148	○		3.0	0.814	◎		3.5	1.34	○	
	1.5	0.203	○		4.0	0.986	○		4.0	1.48	○	
	2.0	0.247	○	15.0	1.2	0.408	○		4.5	1.61	○	
8.0	1.0	0.173	◎		1.5	0.499	◎		20.0	1.5	0.684	◎
	1.2	0.201	×		2.0	0.641	◎			2.0	0.888	◎
	1.5	0.240	◎		2.5	0.771	◎	2.5		1.08	◎	
	2.0	0.296	◎		3.0	0.888	◎	3.0		1.26	◎	
	2.5	0.339	◎		3.5	0.993	◎	3.2		1.33	◎	
	2.7	0.353	×		4.0	1.09	◎	3.5		1.42	◎	
	3.0	0.370	◎		4.5	1.17	○	4.0		1.58	◎	
	3.2	0.379		16.0	1.0	0.370	○	5.0		1.85	○	
9.0	1.0	0.197	○		1.5	0.536	◎	6.0		2.07	○	
	1.2	0.231	×		2.0	0.690	◎	21.7	1.5	0.747	○	
	1.5	0.277	○		2.5	0.832	◎		2.0	0.972	◎	
10.0	1.0	0.222	◎		3.0	0.962	◎		2.8	1.31	◎	
	1.2	0.260	×		3.5	1.08	◎		3.2	1.46	◎	
	1.5	0.314	◎		4.0	1.18	◎		3.7	1.64	◎	
	2.0	0.395	◎		4.5	1.28	○		4.0	1.75	◎	
	2.5	0.462	◎	17.3	2.3	0.851	○		4.5	1.91	◎	
	3.0	0.518	○		2.8	1.00	○		4.7	1.97	◎	
	10.5	1.7	0.369		×	3.2	1.11		○	5.0	2.06	○
2.0		0.419	◎		3.5	1.19	◎	6.0	2.32	○		
2.2		0.450	◎		4.0	1.31	◎	22.0	1.2	0.616	○	
2.4		0.479	◎		4.5	1.42	○		1.5	0.758	◎	
3.0		0.555	○	18.0	1.2	0.497	○		2.0	0.986	◎	
11.0	1.5	0.351	○		1.5	0.610	◎		2.5	1.20	◎	
	2.0	0.444	○		2.0	0.789	◎		3.0	1.41	◎	
12.0	1.2	0.320	×		2.5	0.956	◎		3.5	1.60	◎	
	1.5	0.388	◎		3.0	1.11	◎		4.0	1.78	◎	
	2.0	0.493	◎		3.5	1.25	◎		4.5	1.94	◎	
	2.5	0.586	◎	4.0	1.38	○	5.0		2.10	◎		
	3.0	0.666	◎	23.0	2.0	0.789	◎	5.5	2.24	◎		
	4.0	0.789	○		3.0	1.04	◎	6.0	2.37	○		
13.0	1.2	0.349	○		3.0	1.48	◎					
	1.6	0.450	○									
	2.0	0.543	○									
	2.5	0.647	○									

◎常備材  
○非常備材  
△取扱材

(備考) \*お取引は実貫重量になります

\*材質は S-C と E-C があります ご確認下さい。

# STKM13C (2/2)

## 冷間引抜鋼管

寸法 (mm)		重量	在 庫	寸法 (mm)		重量	在 庫	寸法 (mm)		重量	在 庫	
外径	肉厚	kg/m		外径	肉厚	kg/m		外径	肉厚	kg/m		
25.0	1.5	0.87	○	28.60	2.6	1.67	◎	38.0	1.5	1.35	◎	
	2.0	1.13	◎		3.5	2.17	◎		2.0	1.78	◎	
	2.5	1.39	◎		5.0	2.91	◎		2.5	2.19	◎	
	3.0	1.63	◎		7.0	3.73	◎		3.0	2.59	◎	
	3.5	1.86	◎	30.00	1.2	0.852	○		3.5	2.98	◎	
	4.0	2.07	◎		1.5	1.05	○		4.0	3.35	◎	
	5.0	2.47	◎		2.0	1.38	◎		5.0	4.07	◎	
	5.5	2.64	◎		2.5	1.70	◎		6.0	4.73	◎	
	6.0	2.81	○		3.0	2.00	◎		7.0	5.35	○	
	7.0	3.11	○		3.5	2.29	◎		8.0	5.92	○	
25.4	2.3	1.31			4.0	2.56	◎	9.0	6.44	○		
	2.8	1.56			4.5	2.83	◎	40.0	1.5	1.42	◎	
	3.2	1.75			5.0	3.08	◎		2.0	1.87	◎	
	3.5	1.89			6.0	3.55	○		2.5	2.31	◎	
	4.0	2.11		7.0	3.97	○	3.0		2.74	◎		
	4.5	2.32		8.0	4.34	○	3.5		3.15	◎		
26.0	2.0	1.18	○	32.00	1.5	1.13	◎		4.0	3.55	◎	
	3.0	1.70	○		2.0	1.48	◎		4.5	3.94	◎	
	4.0	2.17	○		2.5	1.82	◎		5.0	4.32	◎	
	5.0	2.59	○		3.0	2.15	◎		6.0	5.03	◎	
	6.0	2.96	○		3.5	2.46	◎		7.0	5.70	◎	
27.2	2.0	1.24	◎		4.0	2.76	◎	45.0	1.5	1.61	◎	
	2.5	1.52	◎		5.0	3.33	◎		2.0	2.12	◎	
	3.0	1.79	◎		6.0	3.85	○		2.5	2.62	◎	
	3.2	1.89	◎		7.0	4.32	○		3.0	3.11	◎	
	3.5	2.05	◎		8.0	4.73	○		3.5	3.58	◎	
	4.0	2.29	◎	34.00	3.0	2.29	◎		4.0	4.04	◎	
	4.5	2.52	◎		35.00	1.5	1.24		◎	5.0	4.93	○
	5.0	2.74	◎	2.0		1.63	◎		6.0	5.77	○	
	5.5	2.94	◎	2.5		2.00	◎		50.0	1.5	1.79	◎
	6.0	3.14	○	3.0		2.37	◎			2.0	2.37	◎
7.0	3.49	○	3.5	2.72		◎	3.0	3.48		◎		
28.0	1.5	0.980	◎	4.0		3.06	◎	4.0		4.54	◎	
	2.0	1.28	◎	5.0	3.70	◎	5.0	5.55		◎		
	2.5	1.57	◎	6.0	4.29	○	55.0	2.0	2.61	△		
	3.0	1.85	◎	8.0	5.33	○		2.5	3.24	○		
	3.5	2.11	◎					3.0	3.85	○		
	4.0	2.37	◎					4.0	5.03	○		
	5.0	2.84	◎					5.0	6.17	○		
	5.0	2.84	◎									
6.0	3.26	○										
7.0	3.63	○										

◎常備材  
○非常備材  
△取扱材

(備考)

\*お取引は実貫重量になります

\*材質は S-C と E-C があります ご確認下さい。