

STKM20A 機械構造用炭素鋼鋼管

SUMISTRONG55H 機械構造用高張力鋼管

寸法(mm)		重量 kg/m	在庫	
外径	肉厚		20A	55H
76.3	6.0	10.4		◎
	8.0	13.5		○
	10.0	16.3		
82.6	10.0	17.9		
	12.0	20.9		
	15.0	25.0		
89.1	6.0	12.3		
	6.6	13.4		○
	8.0	16.0		◎
	10.0	19.5		
101.6	8.0	18.5		
	10.0	22.6		◎
	12.0	26.5		
110.0	10.0	24.7		
	12.0	29.0		
	15.0	35.1		
	16.0	37.1		△
114.3	8.6	22.4	△	
	10.0	25.7		
	12.0	30.3		
120.0	12.0	32.0		
	15.0	38.8		
	16.0	41.0	△	
	20.0	49.3		
130.0	20.0	54.3		△
139.8	15.0	46.2		
	15.9	48.6		
	18.0	54.1		△
	20.0	59.1		
	25.0	70.8		△
146.0	12.0	39.7		
	15.0	48.5		
	20.0	62.1		
152.4	15.0	50.8		
	20.0	65.3		△
	25.0	78.5	△	
159.0	12.0	43.5		△
	15.0	53.3		
	20.0	68.6		△
	25.0	82.6		
165.2	14.3	53.2		◎
	18.0	65.3		△
	20.0	71.6		
	25.0	86.4	△	△
	30.0	100		

寸法(mm)		重量 kg/m	在庫	
外径	肉厚		20A	55H
168.3	11.0	42.7		○
	12.0	46.3		△
	15.0	56.7		
	17.0	63.4		
	18.0	66.7		△
	20.0	73.1		
177.8	15.0	60.2		
	17.0	67.4		
	20.0	77.8		
	25.0	94.2		△
	190.7	12.5	54.9	
190.7	15.0	65.0		
	18.0	76.7		△
	20.0	84.2		△
	23.0	95.1		△
	25.0	102		
205.0	15.0	70.3		
	20.0	91.2		△
	25.0	111		△
	30.0	129		△
	35.0	147		
216.3	12.5	62.8		○
	20.0	96.8		
	24.0	114		△
	25.0	118		
	30.0	138		△
219.1	20.0	98.2		
	23.0	111		△
	25.0	120		△
	30.0	140		
	232.0	20.0	105	
24.0		123		△
25.0		128		
30.0		149		△
35.0		170		
241.8	24.0	129		
	25.0	134		
	30.0	157		△
	35.0	178		

寸法(mm)		重量 kg/m	在庫		
外径	肉厚		20A	55H	
244.5	20.0	111			
	25.0	135	△		
	26.0	140		△	
	30.0	159		△	
267.4	20.0	122			
	25.0	149		△	
	28.6	168		△	
	30.0	176			
	32.0	186		△	
	38.0	215		△	
273.1	40.0	224			
	25.0	153			
	30.0	180		△	
	32.0	190			
	35.0	206			
298.5	25.0	169			
	28.0	187		△	
	30.0	199			
	35.0	227		△	
	38.0	244			
	40.0	255			
318.5	45.0	281			
	25.0	181			
	28.5	204		△	
	30.0	213			
	32.5	229		△	
318.5	35.0	245			
	37.0	257			
	38.0	263		△	
	40.0	275			
	45.0	304			
	339.7	35.0	263		
38.0		283			
40.0		296	△		
355.6	25.0	204			
	30.0	241			
	32.0	255		△	
355.6	35.0	277			
	381.0	25.0	219		
	30.0	260			
	35.0	299			
381.0	40.0	336		△	

◎常備材
○非常備材
△取扱材