

### 【スモール 正方形】

寸 法				重量 kg/m	在庫
T	A	B	L		
1.0	9.0	9.0	4,000	0.289	◎
1.2	11.0	11.0	5,500	0.435	◎
1.6	13.0	13.0	5,500	0.690	◎
1.2	14.0	14.0	5,500	0.530	◎
1.2	16.0	16.0	5,500	0.621	◎
1.6	16.0	16.0	5,500	0.813	◎
1.2	19.0	19.0	5,500	0.716	◎
1.6	19.0	19.0	5,500	0.939	◎
1.2	21.0	21.0	5,500	0.811	◎
1.6	21.0	21.0	5,500	1.07	◎
1.6	24.0	24.0	5,500	0.905	△
1.6	24.0	24.0	5,500	1.19	◎
1.2	25.0	25.0	5,500	0.971	◎
1.6	25.0	25.0	5,500	1.28	◎
R 1.6	25.0	25.0	5,500	1.19	◎
R 1.2	26.0	26.0	5,500	1.44	△
R 1.6	26.0	26.0	5,500	1.19	◎
1.2	28.0	28.0	5,500	1.05	△
1.6	28.0	28.0	5,500	1.44	◎
R 1.2	31.0	31.0	5,500	1.09	◎
R 1.6	31.0	31.0	5,500	1.44	◎
1.2	32.0	32.0	5,500	1.23	◎
1.6	32.0	32.0	5,500	1.62	◎
1.6	38.0	38.0	5,500	1.94	◎
R 1.6	40.0	40.0	5,500	1.94	◎
R 2.0	40.0	40.0	6,000	2.41	◎
1.6	45.0	45.0	5,500	2.32	◎

### 【スモール 長方形】

寸 法				重量 kg/m	在庫
T	A	B	L		
1.2	22.0	10.0	5,500	0.621	◎
1.6	22.0	10.0	5,500	0.813	△
1.2	25.0	12.0	5,500	0.716	◎
1.6	25.0	12.0	5,500	0.939	◎
1.2	28.0	18.0	5,500	0.906	◎
1.6	28.0	18.0	5,500	1.19	◎
R 1.2	30.0	20.0	5,500	0.906	◎
R 1.6	30.0	20.0	5,500	1.19	◎
1.2	32.0	14.0	5,500	0.906	◎
1.6	32.0	14.0	5,500	1.19	◎
1.2	40.0	16.0	5,500	1.09	◎
1.6	40.0	16.0	5,500	1.44	◎
R 1.2	40.0	20.0	5,500	1.09	◎
R 1.6	40.0	20.0	5,500	1.44	◎
1.2	40.0	25.0	5,500	1.23	◎
1.6	40.0	25.0	5,500	1.62	◎
1.6	50.0	18.0	5,500	1.71	◎
1.6	50.0	26.0	5,500	1.94	◎
R 1.6	50.0	30.0	5,500	1.94	◎
1.6	60.0	30.0	5,500	2.32	◎
1.6	60.0	35.0	5,500	2.44	◎
1.6	70.0	25.0	5,500	2.44	◎
R 1.6	75.0	25.0	5,500	2.44	◎
R 1.6	70.0	30.0	5,500	2.44	◎
R 1.6	80.0	40.0	5,500	2.95	◎
2.0	84.0	32.0	5,500	3.66	◎
R 1.6	90.0	30.0	5,500	2.95	◎

◎常備材      ○非常備材      △取扱材

(備考)寸法によりカラー材有ります

# STKR

## 一般構造用角形鋼管

### 【正方形】

寸法			重量 kg/m	在庫
T	A	B		
1.6	50	50	2.38	◎
2.3			3.34	◎
3.2			4.50	◎
4.5			6.02	◎
6.0			7.56	◎
1.6	60	60	2.88	◎
2.3			4.06	◎
3.2			5.50	◎
4.5			7.43	◎
6.0			9.45	◎
2.3	75	75	5.14	◎
3.2			7.01	◎
4.5			9.55	◎
6.0			12.3	◎
8.0			15.5	◎
9.0			17.0	◎
2.3	80	80	5.50	◎
3.2			7.51	◎
4.5			10.3	◎
6.0			13.2	◎
2.3	90	90	6.23	◎
3.2			8.51	◎
4.5			11.7	◎
6.0			15.1	◎
1.6	100	100	4.89	◎
2.3			6.95	◎
3.2			9.52	◎
4.5			13.1	◎
6.0			17.0	◎
9.0			24.1	◎
12.0			30.2	◎

- ◎常備材
- 非常備材
- △取扱材

(備考)  
寸法により 長さ6~12m  
またカラー材あります

### 【正方形】

寸法			重量 kg/m	在庫
T	A	B		
2.3	125	125	8.75	◎
3.2			12.0	◎
4.5			16.6	◎
6.0			21.7	◎
9.0			31.1	◎
12.0			39.7	◎
3.2	150	150	14.5	◎
4.5			20.1	◎
5.0			22.3	◎
6.0			26.4	◎
9.0			38.2	◎
12.0			49.1	◎
4.5	175	175	23.7	◎
6.0			31.1	◎
9.0			45.3	◎
12.0			58.5	◎
4.5	200	200	27.2	◎

### 【エコノミー角】

寸法			重量 kg/m	在庫
T	A	B		
1.6	75	75	3.64	◎
1.6	50	20	1.63	◎
2.3			2.25	◎
3.2			3.12	○
1.6	75	45	2.88	◎
1.6	100	20	2.95	◎
2.3			4.20	◎
1.6	100	40	3.38	◎
2.3			4.78	◎
3.2			6.78	○
1.6	100	50	3.64	◎
1.6	125	40	4.01	◎
2.3			5.69	◎
3.2			7.76	◎
2.3	150	50	6.95	◎
3.2	150	50	9.52	◎

### 【長方形】

寸法			重量 kg/m	在庫
T	A	B		
1.6	60	30	2.13	◎
2.3			2.98	◎
3.2			3.99	◎
4.5			5.31	◎
2.3	75	45	4.06	◎
3.2			5.50	◎
4.5			7.43	◎
4.5	75	50	7.79	◎
6.0			9.92	◎
2.3	100	50	5.14	◎
3.2			7.01	◎
4.5			9.55	◎
6.0			12.3	◎
1.6	125	75	4.89	◎
2.3			6.95	◎
3.2			9.52	◎
4.5			13.1	◎
6.0			17.0	◎
9.0			24.1	◎
3.2	150	75	10.8	◎
4.5			14.9	◎
6.0			19.3	◎
9.0			27.6	△
4.5	150	80	15.2	◎
6.0			19.8	◎
2.3	150	100	8.75	◎
3.2			12.0	◎
4.5			16.6	◎
6.0			21.7	◎
9.0			31.1	◎
12.0			39.7	◎
3.2	200	100	14.5	◎
4.5			20.1	◎
6.0			26.4	◎
9.0			38.2	◎
12.0			49.1	◎
4.5	200	150	23.7	◎
6.0			31.1	◎
9.0			45.3	◎
12.0			58.5	◎

# 特殊角鋼管 その他

## 【特殊角 正方形】

寸法			重量 kg/m	在庫
T	A	B		
2.3	20	20	1.31	◎
3.5	40	40	3.89	◎
4.5			4.89	◎
4.5	50	50	6.02	◎
5.0			6.56	◎
5.5			7.07	◎
4.5	54	54	6.59	◎
4.2	60	60	7.00	◎
5.2			8.40	◎
3.2	63.5	63.5	5.77	◎
4.2			7.46	◎
5.2			8.97	◎
3.2	65	65	6.00	◎
4.2			7.47	◎
5.2			9.12	◎
6.0			10.4	◎
3.2	70	70	6.78	◎
4.2			8.32	◎
5.5			10.5	◎
6.0			11.3	◎
4.2	75	75	8.79	◎
5.5			11.3	◎
6.6			13.4	◎
7.6			15.3	◎
9.0			17.0	◎
4.2	80	80	9.64	◎
5.7			12.6	◎

## 【特殊角 正方形】

寸法			重量 kg/m	在庫
T	A	B		
4.2	85	85	10.1	◎
5.7			13.5	◎
8.1			18.2	◎
6.0	90	90	16.0	△
4.5	95	95	12.2	◎
8.6			22.4	◎
8.6	100	100	22.4	◎
11.0			28.2	◎
12.7			31.8	◎
3.5	110	110	11.5	◎
4.5			15.0	◎
4.5	115	115	15.2	◎
6.0			19.8	◎
6.6			21.7	◎
8.1			25.9	◎
9.5	120	120	30.5	◎
12.7			39.8	◎
4.5	130	130	17.3	◎
4.5	135	135	17.8	◎
7.1			27.5	◎
9.3			35.0	◎
11.0			40.4	◎
4.5	137	137	18.2	◎
4.5	138	138	18.2	◎
10.0	153	153	44.6	◎
5.3	160	160	24.2	◎
4.5	175	175	23.7	△
10.3			52.3	◎
12.7			61.5	◎

## 【スパー角 正方形】

寸法			重量 kg/m	在庫
T	A	B		
2.3	20	20	1.31	◎
2.3	25	25	1.67	◎
3.2			2.26	◎
2.3	30	30	2.03	◎
3.2			2.75	◎
3.2	35	35	3.30	◎
2.3	40	40	2.62	◎
3.2			3.58	◎
3.5			3.89	◎
4.5			4.89	◎
2.3	45	45	3.10	◎
3.2			4.25	◎

◎常備材  
○非常備材  
△取扱材

(備考)  
\*長さは 寸法により 5.5 6.0m  
あります。

\*スパー角に 一部カラー色あります。

## 【スパー角 長方形】

寸法			重量 kg/m	在庫
T	A	B		
2.3	30	20	1.67	◎
2.3	40	20	2.03	◎
3.2			2.75	◎
2.3	50	30	2.62	◎
3.2			3.58	◎
2.3	60	40	3.34	◎
3.2			4.76	◎
2.3	70	30	3.47	◎
1.6	75	20	2.32	◎
2.3			3.30	◎
2.3	80	40	4.20	◎
3.2			5.77	◎
2.3	90	30	4.20	◎
3.2			5.77	◎
2.3	90	45	4.86	◎
3.2			6.68	◎

## 【甲 丸】

寸法			重量 kg/m	在庫
T	A	B		
1.2	15	32	0.811	◎
1.6			1.07	◎
1.6	25	49	1.62	◎
2.3	60	30	2.75	◎
1.6	60	36	2.32	◎
2.0	60	70	3.66	◎
2.0	80	45	3.66	◎
3.2	100	50	6.78	◎
3.5	120	70	9.56	◎
3.5	150	90	11.8	◎
4.5			15.0	◎

## 【オーバル】

寸法			重量 kg/m	在庫
T	A	B		
1.6	22	15	0.690	◎
1.2	40	20	0.906	◎
1.6	40	20	1.19	◎
1.6	50	20	1.44	◎
1.6	60	30	1.71	◎
1.6	72	22	1.94	◎
1.6	76	40	2.32	◎
2.3	76	40	3.30	◎
3.2	76	40	4.52	◎
2.3	95	50	4.20	◎
3.2	120	50	6.78	◎
3.5	150	70	9.56	◎

# 特殊角鋼管 その他

【特殊角 長方形】

寸法			重量 kg/m	在庫
T	A	B		
2.3	40	10	1.67	◎
2.3	50	16	2.29	◎
3.2	50	20	3.12	◎
4.5	50	30	4.61	◎
2.3	50	40	3.10	◎
3.2			4.25	◎
4.5			5.31	◎
3.2	54	24	3.58	◎
4.5			4.89	◎
3.2	55	40	4.52	◎
2.3	60	20	2.75	◎
4.5	60	30	5.31	◎
2.3	60	35	3.30	◎
3.2			4.52	◎
1.6	60	40	2.44	◎
2.0			3.03	◎
4.5			6.02	◎
3.2	60	45	4.76	◎
4.5			6.37	◎
4.5	64	38	6.16	◎
2.3	70	30	3.47	◎
3.2			4.76	◎
2.3	70	40	3.84	◎
3.2			5.27	◎
4.5			7.27	◎
3.2	70	50	5.77	◎
4.2			7.00	◎
4.2	75	45	7.00	◎
5.2			8.40	◎
4.2	75	50	7.47	◎
6.0			9.92	◎
4.2	80	60	8.79	◎
2.0	84	32	3.66	◎

【特殊角 長方形】

寸法			重量 kg/m	在庫
T	A	B		
3.2	90	40	6.68	◎
4.2	90	45	7.99	◎
4.2	90	50	8.79	◎
4.2	90	60	8.79	◎
4.2	90	70	9.64	◎
1.6	100	20	2.90	◎
2.0			3.60	◎
2.3			4.20	◎
3.2	100	40	6.51	◎
4.2			8.32	◎
5.5	100	50	11.4	◎
7.6			15.3	◎
4.2	100	60	10.1	◎
4.2	100	70	10.1	◎
4.5	100	80	11.7	◎
3.2	110	50	7.76	◎
4.5	110	60	10.1	◎
4.5	115	65	12.2	◎
3.2	120	40	7.76	◎
3.5	120	50	9.56	◎
2.3	120	60	6.35	◎
3.5			9.26	◎
4.5			11.7	◎
6.0			15.1	◎
3.2	125	40	7.76	◎
4.2			10.1	◎
3.5	125	55	9.26	◎
6.0	125	65	16.0	◎
9.0	125	75	24.1	◎
3.5	130	50	9.26	◎
4.5	130	50	12.2	◎
3.5	140	40	9.56	◎
6.0	140	50	16.0	◎

【特殊角 長方形】

寸法			重量 kg/m	在庫
T	A	B		
3.5	140	80	11.5	◎
6.0			18.9	◎
3.5	150	70	11.5	◎
6.6	150	80	21.7	◎
8.1			26.3	◎
9.5			29.6	◎
3.5	160	60	11.5	◎
4.5	160	110	17.8	◎
3.5	170	50	11.5	◎
3.5	180	40	11.5	◎
4.5	180	80	17.3	◎
2.0	200	60	8.05	◎
3.7			14.4	◎
4.5	200	70	17.8	◎
4.5	200	75	17.8	◎
5.0			19.8	◎
7.1			27.7	◎
9.3			35.8	◎
4.5	200	150	23.5	◎
4.5	210	50	17.3	◎
4.5	245	100	23.3	◎
5.8			29.7	◎
5.3	250	50	23.5	◎
12.7	250	100	61.5	◎
6.0	250	200	39.5	◎
9.3			60.5	◎
12.7			81.5	◎
6.2	300	100	36.4	◎
10.3	310	210	78.3	◎
6.4	380	200	55.1	◎
7.9			67.7	◎
7.9	400	250	77.6	◎
7.9	500	300	96.0	◎

【フラット】

寸法			重量 kg/m	在庫
T	A	B		
1.2	20	8	0.435	◎
1.2	25	12	0.586	◎
1.6			0.765	◎
1.6	30	15	0.939	◎
1.2	37	14	0.811	◎
1.6			1.07	◎
1.6	40	15	1.19	◎
1.6	40	20	1.28	◎
1.2	46	20	1.09	◎
1.6			1.44	◎

【フラット】

寸法			重量 kg/m	在庫
T	A	B		
1.6	48	20	1.44	◎
1.6	54	28	1.71	◎
1.6	55	20	1.62	◎
1.6	72	12	1.94	◎
1.6	80	25	2.32	◎
2.0	90	50	3.66	◎
3.2			5.77	◎
3.2	110	50	6.78	◎
3.5	150	50	9.56	◎
3.5	180	60	11.8	◎

【半円】

寸法			重量 kg/m	在庫
T	A	B		
1.6	30	15	0.939	◎
2.3			1.31	◎
2.3	33	18	1.41	◎
1.2	40	20	0.906	◎
1.6			1.19	◎
1.6	60	30	1.85	◎
1.6	80	40	2.44	◎
2.0			3.03	◎

【甲山】

寸法			重量 kg/m	在庫
T	A	B		
3.5	125	60	9.56	◎
4.5	150	90	15.0	◎
5.3	210	120	24.2	◎

◎常備材  
○非常備材  
△取扱材

(備考) 長さは 寸法により 5.5 6.0m 有ります。

# STKR

## 一般構造用角形鋼管

### 【コラム】

BCR295				
寸法			重量 kg/m	在庫 295
T	A	B		
4.5	200	200		
6.0			35.6	◎
8.0			46.5	◎
9.0			51.8	◎
12.0			67.0	◎
6.0	250	250	45.0	◎
9.0			65.9	◎
12.0			85.8	◎
16.0			111	◎
6.0	300	300	54.4	◎
9.0			80.1	◎
12.0			105	◎
16.0			136	◎
19.0			158	◎
9.0	350	350	94.2	◎
12.0			123	◎
16.0			161	◎
19.0			188	◎
22.0			214	◎
9.0	400	400	108	◎
12.0			142	◎
16.0			186	◎
19.0			218	◎
22.0			248	◎
25.0				
12.0	450	450	161	◎
16.0			211	◎
19.0			247	◎
22.0			283	◎
25.0				
12.0	500	500	180	◎
16.0			236	◎
19.0			277	◎
22.0			317	◎
25.0				
16.0	550	550	261	◎
19.0			307	◎
22.0			352	◎
25.0				

### 【コラム】

STKR400・490					
寸法			重量 kg/m	在庫	
T	A	B		400	490
4.5	200	200	27.2	◎	
6.0			35.8	◎	
8.0			46.9	◎	
9.0			52.3	◎	◎
12.0			67.9	◎	◎
6.0	250	250	45.2	◎	
9.0			66.5	◎	◎
12.0			86.8	◎	◎
16.0			112	*	◎
6.0	300	300	54.7	◎	
9.0			80.6	◎	◎
12.0			106	◎	◎
16.0			138	*	◎
19.0			160	*	◎
9.0	350	350	94.7	◎	◎
12.0			124	*	◎
16.0			163	*	◎
19.0			190	*	◎
22.0			217	*	
9.0	400	400	109	◎	
12.0			143	*	
16.0			188	*	◎
19.0			220	*	◎
22.0			251	*	◎
25.0			282	*	
12.0	450	450	162	*	
16.0			213	*	◎
19.0			250	*	◎
22.0			286	*	◎
25.0			321	*	
12.0	500	500	181	*	
16.0			238	*	◎
19.0			280	*	◎
22.0			320	*	◎
25.0			360	*	
16.0	550	550	263	*	
19.0			310	*	
22.0			355	*	
25.0			399	*	

### 【ワイド角】

STKR400				
寸法			重量 kg/m	在庫 400
T	A	B		
10.3	250	100	51.1	◎
6.0	250	100	35.8	◎
9.0			52.3	◎
12.0			67.9	◎
9.0	300	100	52.3	◎
6.0	300	150	40.5	◎
9.0			59.4	◎
12.0			77.3	◎
6.0	300	200	45.2	◎
9.0			66.5	◎
12.0			86.8	◎
6.0	350	150	45.2	◎
9.0			66.5	◎
12.0			86.8	◎
12.0	350	250	106.0	◎
6.0	400	200	54.7	◎
9.0			80.6	◎
12.0			106.0	◎
12.0	400	300	124.0	◎
9.0	500	300	109.0	◎
9.5			117.0	◎
12.0	500	300	143.0	◎
12.7			155.0	◎
16.0	600	300	211.0	◎
6.9	300	200	53.0	
7.9			60.5	
10.3	310	210	78.3	
12.7			95.8	
6.4	380	200	55.1	
7.9			67.7	
12.7			107	
7.9	400	250	77.6	
8.0			78.6	
19.0			182	
12.0	410	100	90.7	
7.9	500	300	97.4	
9.5	600	200	117	
12.7			155	

(備考) 長さ6~12M有ります

◎常備材 ○非常備材 △取扱材 \*受注生産

(備考) 建築構造用冷間成形角形鋼管 『BCR BCP』

SN材(建築構造用鋼材)をベースとした大臣認定品で JIS規格(STKR)より高品質・高性能 製品です。

BCR295 365は冷間ロール成形 BCP235 325 325Tは冷間プレス成形、BCR295以外はオーダーメイドが基本です。