

SUMISTRONG55H 機械構造用高張力鋼管 STKM20A 機械構造用炭素鋼鋼管

寸法(mm)		重量 kg/m	在庫	
外径	肉厚		55H	20A
76.3	6.0	10.4	◎	
	8.0	13.5	○	
	10.0	16.3		
82.6	10.0	17.9		
	12.0	20.9		
	15.0	25.0		
89.1	6.0	12.3		
	6.6	13.4		
	8.0	16.0	◎	
	10.0	19.5		
101.6	8.0	18.5		
	10.0	22.6	◎	
	12.0	26.5		
110.0	10.0	24.7		
	12.0	29.0		
	15.0	35.1		
	16.0	37.1	△	
114.3	8.6	22.4		◎
	10.0	25.7		
	12.0	30.3		
120.0	12.0	32.0		
	15.0	38.8		
	16.0	41.0		△
	20.0	49.3		
130.0	20.0	54.3	△	
139.8	15.0	46.2		
	15.9	48.6		
	18.0	54.1	△	
	20.0	59.1		
	25.0	70.8	△	
146.0	12.0	39.7		
	15.0	48.5	△	
	20.0	62.1		
152.4	15.0	50.8		
	20.0	65.3	△	
	25.0	78.5		◎
159.0	12.0	43.5	△	
	15.0	53.3		
	20.0	68.6	△	
	25.0	82.6		
165.2	14.3	53.2	◎	
	18.0	65.3	△	
	20.0	71.6		
	25.0	86.4	△	◎
	30.0	100		

寸法(mm)		重量 kg/m	在庫	
外径	肉厚		55H	20A
168.3	11.0	42.7	○	
	12.0	46.3	△	
	15.0	56.7		
	17.0	63.4		
	18.0	66.7	△	
	20.0	73.1		
177.8	15.0	60.2		
	17.0	67.4		◎
	20.0	77.8		
	25.0	94.2	△	
190.7	12.5	54.9	○	
	15.0	65.0		
	18.0	76.7	△	
	20.0	84.2	△	
	23.0	95.1	△	
205.0	15.0	70.3		
	20.0	91.2	△	
	25.0	111	△	
	30.0	129	△	
	35.0	147		
216.3	12.5	62.8	○	
	20.0	96.8		
	24.0	114	△	
	25.0	118		
219.1	20.0	98.2		
	23.0	111	△	
	25.0	120	△	
	30.0	140		
232.0	20.0	105		
	24.0	123	△	
	25.0	128		
	30.0	149	△	
	35.0	170		
241.8	24.0	129		
	25.0	134		
	30.0	157	△	
	35.0	178		

◎常備材  
○非常備材  
△取扱材

寸法(mm)		重量 kg/m	在庫	
外径	肉厚		55H	20A
244.5	20.0	111		
	25.0	135		○
	26.0	140	△	
	30.0	159	△	
267.4	20.0	122		
	25.0	149	△	
	28.6	168	△	
	30.0	176		
	32.0	186	△	
	38.0	215	△	
273.1	25.0	153		
	30.0	180	△	
	32.0	190		
	35.0	206		
	298.5	25.0	169	
28.0		187	△	
30.0		199		
35.0		227	△	
38.0		244		
40.0		255		
318.5	25.0	181		
	28.5	204	△	
	30.0	213		
	32.5	229	△	
	35.0	245		
	37.0	257		
	38.0	263	△	
40.0	275			
339.7	35.0	263		
	38.0	283		
	40.0	296		△
355.6	25.0	204		
	30.0	241		
	32.0	255	△	
	35.0	277		
381.0	25.0	219		
	30.0	260		
	35.0	299		
	40.0	336	△	